

Installing Guide and Installing Precautions

Multifunction Navi and Entertainment System
for Honda Accord(European Version)



Installation of Honda Accord (European Version)



1. The diagram of original radio system



2. Pry the buckles of decorative plate with the crow plate (mind the buckles)



3. Remove the decorative plate and disconnect the wiring (mind the buckles and wiring)



4. Pry the screw with screwdriver as shown picture



5. Pry the buckles of decorative plate with the crow plate and remove



6. Pry the buckles of decorative plate with the crow plate and remove



7. Pry the screws fixing the decorative board with screwdriver



8. Pry the buckles of decorative plate with the crow plate and remove

Installation of Honda Accord (European Version)



9. Pry the buckles of decorative plate with the crow bar and remove then remove the screws under the glovebox



10. Pry the screw over the glovebox and take out the glovebox



11. Remove the ash tray



12. Pry the screw under the ash tray and remove the cigar lighter, then disconnect the wires



13. Pry the screws fixing for the air conditioner and glovebox



14. Take out the air conditioner and glovebox, then disconnect the wires



15. Pry the buckles of the original screen with crow plate



16. Pry the two screws in the picture and disconnect the wires

Installation of Honda Accord (European Version)



17.A. GPS screen and DVD part
B. AV cables C. Speaker cable
D. DVD connection wires



18. Take out the speaker cable as shown picture



19. Install the DVD switch cable as shown picture, the upper cable should be pulled through the mantle



20. Install the AV cables as shown picture



21. Connect the REMOTE cable with the 21th thin pink cable of the original system with insulating cloth



22. Connect the speaker cable with the original speaker cable



23. Connect the wires on the big panel



24. Install the big panel and fix with the screws

Installation of Honda Accord (European Version)



25. Take off the 4 buckles on the original screen



26. Install the buckles on the GPS system



27. Install the USB cable of GPS as shown picture



28. Connect the cables of the GPS system



29. Install the GPS screen and connect the wires



30. Connect the DVD connection wires with the DVD part



31. Fix the 4 screws on the DVD head unit



32. Fix the air conditioner

Installation of Honda Accord (European Version)



33. Fix the cigar lighter



34. Fix the cigar lighter with screws and install the ash tray



35. Put the USB connection wire in the glovebox



36. Install the glovebox and fix with the upper screws



37. Fix the screws under the glovebox, then install the side cover plate



38. Install the right decorative plate and fix with screws



39. Install the upper decorative plate of the glovebox



40. Install the left decorative plate and fix with the screws.

Installation of Honda Accord (European Version)



41. Install the decorative plate as picture shows



42. The diagram after installing.

■ Warm Tips

1. Don't use strong chemical products, cleaning agents or detergents to clean the unit.
2. Please use soft and clean cloth to clean the screen; it's advised not to use paper to clean.
3. LED screen is easy to be scratched, please use touch pen to make operations. Don't use sharp objects to write on the screen to avoid screen damage.
4. Do not maintain or install the unit by yourself under the power on condition., especially dangerous if operated by the person without the trading or experiences of electronic equipment and car accessories installation.
5. Before installation, please confirm with the car owner the original car audio system works and with no scratches.
6. Please protect the meters of the vehicle and the remaining parts, and install the the parts not needed to the car.
7. Navigation and rearview camera is only for driving assistant and can not replace your attention and judgement.

■ Install GPS Antenna

GPS antenna may be installed inside the car such as on the dash—board or coat rack; it may be also installed outside the car such as the top of car or on the trunk lid.

GPS antenna must have an open “visual field” towards the sky. If the glass of the car window is equipped with explosionproof film or heat insulation film, it might greatly reduce the receiving strength; in that case it's advised to install the GPS antenna outside the car.

▲ Precautions:

- ◆ Do not shorten or extend the GPS antenna, or short circuit or antenna fault may be caused.
- ◆ When install GPS antenna, please ensure the antenna is in same horizontal plane, or it may effect the precision of navigation positioning.
- ◆ Avoid the twine of GPS antenna or the interference to the steering wheel or gearlever, or dangerous may be caused.
- ◆ Only the professional installing technicians are allowed to install and maintain this product.
- ◆ Installation or maintenance by the laypeople might cause electric shock or other risks and even damage the unit.
- ◆ In the process of connecting connector, pay attention to the hook position, don't pull wires forcibly to avoid invalid connection;
- ◆ Please use the attached wire of the system, otherwise the accident of fire or smoke or damage to the unit or vehicle might be caused;
- ◆ Don't cut off any extra wire which is kept for future use.
Protect the ends of wire with insulating tape;
- ◆ In order to avoid short circuit, please disconnect the anode of the power accumulator before any connection and installation;
- ◆ Ensure all lines are placed and protected in good condition, don't let them interfere in any moveable parts of the car such as steering wheel, gearlever, brake pedal, sliding chair, door or other parts;
- ◆ The voice is input through AUX, so please ensure audio cable connects well with the AUX port of the original car audio system
- ◆ This Teana GPS can be fit for new Teana 2.0 Comfort Edition, 2.0 GT Edition and 2.4 Comfort Edition